



SUBMERSIBLE PUMPS & MOTORS

SGS SERIES (60 Hz)
North America



Contents

	Page No.
Introduction	02
Features	02
Applications	02
Material specifications	02
Type key	03
Performance curve & Technical Data	
4" Submersible Pumps	
5 SGS	05-06
7 SGS	07-08
10 SGS	09-10
13 SGS	11-12
18 SGS	13-14
25 SGS	15-16
40 SGS	17-18
50 SGS	19-20
66 SGS	21-22
85 SGS	23-24

INTRODUCTION

Shakti 4ss pumps series is a robust 4" pumps designed for long life operation, it is built mainly in a special Floating type impeller the design is to enhance the overall performance of pumps.

The optimal design of impeller and diffuser enables the best possible hydraulic efficiency. Built-in check valve prevents back flow and reduces the risk of water hammering. All vital components of these pumps are made up of corrosive resistance thermoplastic and the shaft is of SS 304.

FEATURES

- Simple installation and maintenance free
- Pump impellers are floating type.
- High efficiency design for low operation cost.
- Longer and trouble free life
- Wide hydraulic range.

APPLICATIONS

- Domestic & Residential water supply
- Gardening and Small Farm Irrigation
- Washing systems
- Civil Applications use.
- Fountains

MATERIAL SPECIFICATION


Components	Material
Pump Outer Sleeve	AISI SS 304
Discharge Casing	AISI SS 304
Suction Casing	AISI SS 304
Diffuser	Noryl (PC)
Impeller	Noryl (POM)
Pump Shaft	AISI SS 304
Shaft Coupling	AISI SS 304
Wear Ring	AISI SS 304

TYPE KEY



EXAMPLE

PUMP 13SGS05 - 4 (4x4)1.25" NPT



Performance Curve and Technical Data


4 Inch Submersibles

PERFORMANCE CURVE



SUBMERSIBLE PUMPS 5 SGS

5 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

TECHNICAL DATA

SUBMERSIBLE PUMPS 5 SGS

5 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
5SGS05- 9	A	0.5	4"	1	1.25"	27.2	13.5	13.7	3.8	3.9	6.1	28.4
5SGS05- 12	A	0.5	4"	1	1.25"	29.2	13.5	15.7	3.8	3.9	7.0	28.4
5SGS07- 15	A	0.75	4"	1	1.25"	32.4	14.6	17.8	3.8	3.9	8.0	32.8
5SGS10- 20	A	1	4"	1	1.25"	38.1	15.5	22.6	3.8	3.9	10.2	28.4
5SGS15- 26	A	1.5	4"	1	1.25"	44.1	17.4	26.7	3.8	3.9	12.7	32.9




FIG. A

3 WIRE


MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
5SGS05- 9	A	0.5	4"	1	1.25"	23.1	9.4	13.7	3.8	3.9	6.1	19.3
				3		24.2	10.5		3.8			22.2
5SGS05- 12	A	0.5	4"	1	1.25"	25.1	9.4	15.7	3.8	3.9	7.0	19.3
				3		26.2	10.5		3.8			22.2
5SGS07- 15	A	0.75	4"	1	1.25"	29.1	11.3	17.8	3.8	3.9	8.0	24.3
				3		28.2	10.4		3.8			22.2
5SGS10- 20	A	1	4"	1	1.25"	33.9	11.3	22.6	3.8	3.9	10.2	24.3
				3		33.9	11.3		3.8			24.3
5SGS15- 26	A	1.5	4"	1	1.25"	39.9	13.2	26.7	3.8	3.9	12.7	28.7
				3		39.9	13.2		3.8			28.7
5SGS20- 33	A	2	4"	1	1.25"	47.3	15.7	31.6	3.8	3.9	15.0	34.6
				3		47.3	15.7		3.8			34.6

PERFORMANCE CURVE



SUBMERSIBLE PUMPS 7 SGS

7 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 7 SGS

7 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
7SGS05- 6	A	0.5	4"	1	1.25"	28.6	13.5	15.1	3.8	3.9	6.8	28.4
7SGS05- 8	A	0.5	4"	1	1.25"	30.9	13.5	17.4	3.8	3.9	7.8	28.4
7SGS07- 10	A	0.75	4"	1	1.25"	33.4	14.6	18.8	3.8	3.9	8.5	32.8
7SGS10- 13	A	1	4"	1	1.25"	37.2	15.5	21.7	3.8	3.9	9.7	28.4
7SGS15- 18	A	1.5	4"	1	1.25"	46.2	17.4	28.8	3.8	3.9	13.67	32.9




FIG. A

3 WIRE


MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
7SGS05- 6	A	0.5	4"	1	1.25"	24.5	9.4	15.1	3.8	3.9	6.8	19.3
				3		25.6	10.5		3.8			22.2
7SGS05- 8	A	0.5	4"	1	1.25"	26.8	9.4	17.4	3.8	3.9	7.8	19.3
				3		27.9	10.5		3.8			22.2
7SGS07- 10	A	0.75	4"	1	1.25"	30.1	11.3	18.8	3.8	3.9	8.5	24.3
				3		29.2	10.4		3.8			22.2
7SGS10- 13	A	1	4"	1	1.25"	33.0	11.3	21.7	3.8	3.9	9.7	24.3
				3		33.0	11.3		3.8			24.3
7SGS15- 18	A	1.5	4"	1	1.25"	42.0	13.2	28.8	3.8	3.9	13.7	28.7
				3		42.0	13.2		3.8			28.7
7SGS20- 24	A	2	4"	1	1.25"	50.6	15.7	34.9	3.8	3.9	16.5	34.6
				3		50.6	15.7		3.8			34.6
7SGS30- 30	A	3	4"	1	1.25"	63.0	21.5	41.5	3.8	3.9	19.7	48.2
				3		63.0	21.5		3.8			48.2

PERFORMANCE CURVE



SUBMERSIBLE PUMPS 10 SGS

10 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 10 SGS

10 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
10SGS05- 7	A	0.5	4"	1	1.25"	29.3	13.5	15.7	3.8	3.9	7.3	28.4
10SGS07- 10	A	0.75	4"	1	1.25"	33.5	14.6	18.8	3.8	3.9	8.7	32.8
10SGS10- 13	A	1	4"	1	1.25"	37.2	15.5	21.7	3.8	3.9	10	28.4
10SGS15- 17	A	1.5	4"	1	1.25"	45.2	17.4	27.8	3.8	3.9	12.8	32.9




FIG. A

3 WIRE


MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
10SGS05- 7	A	0.5	4"	1	1.25"	25.1	9.4	15.7	3.8	3.9	7.3	19.3
				3		26.2	10.5		3.8			22.2
10SGS07- 10	A	0.75	4"	1	1.25"	30.1	11.3	18.8	3.8	3.9	8.7	24.3
				3		29.2	10.4		3.8			22.2
10SGS10- 13	A	1	4"	1	1.25"	33.0	11.3	21.7	3.8	3.9	10	24.3
				3		33.0	11.3		3.8			24.3
10SGS15- 17	A	1.5	4"	1	1.25"	41.0	13.2	27.8	3.8	3.9	12.8	28.7
				3		41.0	13.2		3.8			28.7
10SGS20- 20	A	2	4"	1	1.25"	46.6	15.7	30.9	3.8	3.9	14.2	34.6
				3		46.6	15.7		3.8			34.6
10SGS30- 27	A	3	4"	1	1.25"	58.4	21.5	36.9	3.8	3.9	17	48.2
				3		58.4	21.5		3.8			48.2

PERFORMANCE CURVE



SUBMERSIBLE PUMPS 13 SGS

13 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 13 SGS

13 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
13 SGS05- 4	A	0.5	4"	1	1.25"	28.6	13.5	15.1	3.8	3.9	6.8	28.4
13SGS07- 6	A	0.75	4"	1	1.25"	29.7	14.6	15.1	3.8	3.9	6.8	32.8
13SGS10- 9	A	1	4"	1	1.25"	34.3	15.5	18.8	3.8	3.9	8.5	28.4
13SGS15- 11	A	1.5	4"	1	1.25"	37.2	17.4	19.8	3.8	3.9	8.9	32.9




FIG. A


3 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
13 SGS05- 4	A	0.5	4"	1	1.25"	24.5	9.4	15.1	3.8	3.9	6.8	19.3
				3		25.6	10.5		3.8			22.2
13SGS07- 6	A	0.75	4"	1	1.25"	26.4	11.3	15.1	3.8	3.9	6.8	24.3
				3		25.5	10.4		3.8			22.2
13SGS10- 9	A	1	4"	1	1.25"	30.1	11.3	18.8	3.8	3.9	8.5	24.3
				3		30.1	11.3		3.8			24.3
13SGS15- 11	A	1.5	4"	1	1.25"	33.0	13.2	19.8	3.8	3.9	8.9	28.7
				3		33.0	13.2		3.8			28.7
13SGS15- 15	A	2	4"	1	1.25"	40.3	15.7	24.6	3.8	3.9	11.1	34.6
				3		40.3	15.7		3.8			34.6
13SGS20- 20	A	3	4"	1	1.25"	52.4	21.5	30.9	3.8	3.9	14.5	48.2
				3		52.4	21.5		3.8			48.2

PERFORMANCE CURVE

SUBMERSIBLE PUMPS 18 SGS

18 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 18 SGS

18 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
18 SGS07- 6	A	0.75	4"	1	1.25"	30.3	14.6	15.7	3.8	3.9	6.9	32.8
18 SGS10- 8	A	1	4"	1	1.25"	33.6	15.5	18.1	3.8	3.9	8	28.4
18 SGS15-11	A	1.5	4"	1	1.25"	39.5	17.4	22.1	3.8	3.9	9.7	32.9




FIG. A


3 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
18 SGS07- 6	A	0.75	4"	1	1.25"	27.0	11.3	15.7	3.8	3.9	6.9	24.3
				3		26.1	10.4		3.8			22.2
18 SGS10- 8	A	1	4"	1	1.25"	29.4	11.3	18.1	3.8	3.9	8	24.3
				3		29.4	11.3		3.8			24.3
18 SGS15-11	A	1.5	4"	1	1.25"	35.3	13.2	22.1	3.8	3.9	9.7	28.7
				3		35.3	13.2		3.8			28.7
18 SGS20- 15	A	2	4"	1	1.25"	43.5	15.7	27.8	3.8	3.9	12.2	34.6
				3		43.5	15.7		3.8			34.6
18 SGS30- 20	A	3	4"	1	1.25"	52.4	21.5	30.9	3.8	3.9	14.5	48.2
				3		52.4	21.5		3.8			48.2

PERFORMANCE CURVE

SUBMERSIBLE PUMPS 25 SGS

25 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 25 SGS

25 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
25 SGS07- 4	A	0.75	4"	1	1.25"	29.7	14.6	15.1	3.8	3.9	6.5	32.8
25 SGS10- 6	A	1	4"	1	1.25"	31.2	15.5	15.7	3.8	3.9	6.8	28.4
25 SGS15- 9	A	1.5	4"	1	1.25"	37.2	17.4	19.8	3.8	3.9	8.5	32.9




FIG. A


3 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
25 SGS07- 4	A	0.75	4"	1	1.25"	26.4	11.3	15.1	3.8	3.9	6.5	24.3
				3		25.5	10.4		3.8			22.2
25 SGS10- 6	A	1	4"	1	1.25"	27.0	11.3	15.7	3.8	3.9	6.8	24.3
				3		27.0	11.3		3.8			24.3
25 SGS15- 9	A	1.5	4"	1	1.25"	33.0	13.2	19.8	3.8	3.9	8.5	28.7
				3		33.0	13.2		3.8			28.7
25 SGS20- 11	A	2	4"	1	1.25"	37.8	15.7	22.1	3.8	3.9	9.9	34.6
				3		37.8	15.7		3.8			34.6
25 SGS30- 15	A	3	4"	1	1.25"	49.3	21.5	27.8	3.8	3.9	12.5	48.2
				3		49.3	21.5		3.8			48.2

PERFORMANCE CURVE

SUBMERSIBLE PUMPS 40 SGS

40 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 40 SGS

40 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
40 SGS10- 4	A	1	4"	1	1.5"	30.6	15.5	15.1	3.8	3.9	6.8	28.4
40 SGS15- 6	A	1.5	4"	1	1.5"	34.8	17.4	17.4	3.8	3.9	7.8	32.9




FIG. A


3 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
40 SGS10- 4	A	1	4"	1	1.5"	26.4	11.3	15.1	3.8	3.9	6.8	24.3
				3		26.4	11.3		3.8	3.9		24.3
40 SGS15- 6	A	1.5	4"	1	1.5"	30.6	13.2	17.4	3.8	3.9	7.8	28.7
				3		30.6	13.2		3.8	3.9		28.7
40 SGS20- 8	A	2	4"	1	1.5"	37.8	15.7	22.1	3.8	3.9	9.9	34.6
				3		37.8	15.7		3.8	3.9		34.6
40 SGS30- 12	A	3	4"	1	1.5"	49.3	21.5	27.8	3.8	3.9	12.5	48.2
				3		49.3	21.5		3.8	3.9		48.2
40 SGS50- 19	A	5	4"	1	1.5"	65.9	27.4	38.5	3.8	3.9	17.3	65.1
				3		61.5	23.0		3.8	3.9		65.1
40 SGS75- 25	A	7.5	4"	3	1.5"	76.2	30.5	45.7	3.8	3.9	20.6	72.9

PERFORMANCE CURVE

SUBMERSIBLE PUMPS 50 SGS

50 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 50 SGS

50 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
50 SGS10- 3	A	1	4"	1	2.0"	30.6	15.5	15.1	3.8	3.9	6.8	28.4
50 SGS15- 4	A	1.5	4"	1	2.0"	32.5	17.4	15.1	3.8	3.9	6.8	32.9




FIG. A

3 WIRE


MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
50 SGS10- 3	A	1	4"	1	2.0"	26.4	11.3	15.1	3.8	3.9	6.8	24.3
				3		26.4	11.3		3.8	3.9		24.3
50 SGS15- 4	A	1.5	4"	1	2.0"	28.3	13.2	15.1	3.8	3.9	6.8	28.7
				3		28.3	13.2		3.8	3.9		28.7
50 SGS20- 5	A	2	4"	1	2.0"	33.9	15.7	18.2	3.8	3.9	8.2	34.6
				3		33.9	15.7		3.8	3.9		34.6
50 SGS30- 8	A	3	4"	1	2.0"	43.6	21.5	22.1	3.8	3.9	9.9	48.2
				3		43.6	21.5		3.8	3.9		48.2
50 SGS50- 12	A	5	4"	1	2.0"	56.2	27.4	28.8	3.8	3.9	13	65.1
				3		51.8	23.0		3.8	3.9		65.1
50 SGS75- 18	A	7.5	4"	3	2.0"	69.0	30.5	38.5	3.8	3.9	17.3	72.9

PERFORMANCE CURVE



SUBMERSIBLE PUMPS 66 SGS

66 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 66 SGS

66 GPM

Dimensions and Weights:-

3 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
66 SGS20- 5	A	2	4"	1	2.0"	35.5	15.7	19.8	3.8	3.9	8.9	34.6
				3		35.5	15.7		3.8	3.9		34.6
66 SGS30- 7	A	3	4"	1	2.0"	49.3	21.5	27.8	3.8	3.9	12.5	48.2
				3		49.3	21.5		3.8	3.9		48.2
66 SGS50- 12	A	5	4"	1	2.0"	64.3	27.4	36.9	3.8	3.9	16.6	65.1
				3		59.9	23.0		3.8	3.9		65.1
66 SGS75- 18	A	7.5	4"	3	2.0"	82.1	30.5	51.6	3.8	3.9	23.2	72.9





FIG. A

PERFORMANCE CURVE

SUBMERSIBLE PUMPS 85 SGS

85 GPM



Specifications subject to change without notice.
4" Motor Standard, 3450 RPM

Performance conforms to ISO 9906 annex A

SUBMERSIBLE PUMPS 85 SGS

85 GPM

Dimensions and Weights:-

2 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
85 SGS15- 2	A	1.5	4"	1	2.0"	33.2	17.4	15.8	3.8	3.9	7.1	32.9





FIG. A

3 WIRE

MODEL NO.	FIG.	HP	MOTOR SIZE	Ph	DISCH. SIZE (NPT) Rp	DIMENSIONS IN INCHES					APPROX SHIPPING WEIGHT (lbs)	
						A	B	C	D	E	PUMP	MOTOR
85 SGS15- 2	A	1.5	4"	1	2.0"	29.0	13.2	15.8	3.8	3.9	7.1	28.7
				3		29.0	13.2		3.8	3.9		28.7
85 SGS20- 3	A	2	4"	1	2.0"	33.9	15.7	18.2	3.8	3.9	8.2	34.6
				3		33.9	15.7		3.8	3.9		34.6
85 SGS30- 4	A	3	4"	1	2.0"	43.2	21.5	21.7	3.8	3.9	9.8	48.2
				3		43.2	21.5		3.8	3.9		48.2
85 SGS50- 8	A	5	4"	1	2.0"	62.3	27.4	34.9	3.8	3.9	15.7	65.1
				3		57.9	23.0		3.8	3.9		65.1
85 SGS75- 11	A	7.5	4"	3	2.0"	72.0	30.5	41.5	3.8	3.9	18.7	72.9



SAP No. 2000021212

Jan. 2024/R7

Jan./2025-26/L2/000 VC - 0000



SHAKTI PUMPS USA LLC.

740, Florida Central Parkway, Suite # 1008, Longwood, FL 32750, USA
 Ph: 407 574 4001, 407 574 2797,
 E-mail: usa@shaktipumps.com, Visit us at: www.shaktipumps.us